

# CYBERVIEW

## RKPI415/1417/1419

### SERIES



#### LCD Keyboard Drawer

- 1U 15", 17" or 19" TFT LCD Screen
- Two Keyboard selections "e" and "b" support multiple languages
- Optional integrated KVM
- Minimum rack space required
- Short depth of 440mm for 600mm deep racks

CyberView RKPI415 / 1417 / 1419 Series A 1U rack mountable LCD, keyboard drawer designed to fit 600mm deep racks.

#### PRODUCT FEATURES & BENEFITS

##### IU LCD Screen/Keyboard Drawer

Space saving 1U design, incorporating LCD screen & keyboard 15" / 17" / 19"

**TFT LCD Screen** Available in 3 LCD screen sizes, all in a 1U unit

##### Built in on screen display controlled by integral membrane switches

Allows adjustment of color, contrast, brightness, H Position, V position, Auto Configure, OSD, etc

##### Unique modular mechanical design

Allows easy component level replacement and provides a KVM migration path

##### Extended Slide rails provide clearance distance between rack panel mounts and the rear of the LCD Screen

Allows protruding equipment i.e. servers and patch panels to be mounted directly above the drawer, without interference

##### Slide rails have two friction stops to prevent movement of the keyboard

Allowing comfortable working on unit while maintaining safety practices

##### A selection of keyboards and mouse options

Available with notebook keyboard and either trackball or touchpad mouse

##### Full selection of keyboard languages

Available in European (UK), US, Spanish, German, French, Italian & Norwegian

##### All mounting hardware included

Allows simple, quick and secure installation

#### THE CYBERVIEW SOLUTION...

CyberView offers its users a flexible, space saving, cost effective method of managing multiple servers from a single unit, either locally within the data centre, or remotely via the World Wide Web using secure IP access.


CyberView is available in 1U and 2U height options, depths include 440mm for 600 deep racks or 650mm for 800 deep racks, with complete unit configuration flexibility of simply LCD drawer; Keyboard drawer; LCD Keyboard Drawer or LCD Keyboard Drawer with KVM (Keyboard, Video and Mouse) switch.

To cater for today's ever demanding working environments and applications CyberView is available in 15, 17 or 19" LCD screens with a wide selection of keyboard layouts and languages, including vendor application specific units i.e. full SUN Microsystems Solaris v10 compatibility when using our S Series solutions.


Panel	15" LCD Series	17" LCD Series	19" LCD Series
Display Type	Active matrix TFT colour LCD	Active matrix TFT colour LCD	Active matrix TFT colour LCD
Max Resolution	1024 x 768 XGA	1280 x 1024 SXGA	1280 x 1024 SXGA
Pixel Pitch	0.297(H) x 0.297(W) mm	0.264(H) x 0.264(W) mm	0.294(H) x 0.294(W) mm
Contrast Ratio	300:1	500:1	700:1
Brightness	450 cd / m2	300 cd / m2	300 cd / m2
Response Time	Tr=5 / Tf=20 ms	Tr=3 / Tf=10 ms	Tr=15 / Tf=10ms
Display Colours	16.2M	16.2M	16.7M
Viewing Angle (Typical)	140 (Horiz.) / 115 (Vert.)	150 (Horiz.) / 135 (Vert.)	150 (Horiz.) / 135 (Vert.)
Operating Temp (oc)	0 to 50	0 to 50	0 to 50
Storage Temp (oc)	-25 to 60	-25 to 60	-25 to 60

'E' Type Keyboard	'B' Type Keyboard
-------------------	-------------------

Notebook with touch pad mouse



Notebook with trackball mouse



Unit Type	15" Unit	17" Unit	19" Unit	-----
Unit Dimensions (Cm)	44.2 x 4.45 x 44	44.2 x 4.45 x 44	44.2 x 4.45 x 48	-----
Packaged Dimensions (Cm)	69 x 18 x 57	69 x 18 x 57	69 x 18 x 57	-----
Unit Weight (Kg)	14	15	17	-----
Packaged Weight (Kg)	16	17	19	-----

Power Supply	
Remote adapter	110v-220v ac input - 12v 5a output
Adapter size	10.8(l) x 6.1 (w) x 3(h) cm
Cable length (mains to adapter)	182cm
Cable length (adapter to unit)	180cm
Safety approval	ul / ce



**Technical Information.**

All information contained in this information sheet was correct at the time of going to press. Images are used for illustration purposes and are subject to change at the manufacturers discretion. E&OE.