

POWER DISTRIBUTION MT3 SERIES



Patent pending rPower™ RS232 remote power management is compatible with industry standard console port switches. The high resolution Easy-Read™ ammeter can be read through an enclosure door's perforation.



MT3 Series - 16A, 3 Phase Vertical Power Distribution

- **High-density configurations** reduce enclosure space requirement
- **Fuse-less design** significantly reduces reset time
- **Breaker-less design** meets EN 60950 requirements
- **Easy-Read™ digital ammeter** reduces local monitoring time (auto-scroll capability)
- **rPower™ RS232 remote power management** simplifies monitoring
- **Multi-purpose mounting** improves installation flexibility
- **Isolation hardware** improves product grounding
- **High-grade components** increases product reliability
- **Clearly labeled circuits** simplify load balancing

Designed for high-density, mission critical server applications, the MT3 Series provides maximum power for both standard and blade servers. Employing multiple configurations, the Easy-Read™ digital ammeter, rPower™ RS232 remote power management and clearly labeled circuits, MT3 assures easy management and monitoring for current requirements and future expansion.

Vertical Power Distribution Units

Part Number	Source		Power Lead	Outlets		Dimensions			Power * Watts	Estimated Server Quantity **		
	Volts	Amps	Plug	Type	Qty	W mm	Hmm	D mm		550w	1,000w	2,500w
MT3 - 10666	400/3P (230/1P)	16	IEC309	C13	48	55	1727	51	11,085	33	18	
MT3 - 10667	400/3P (230/1P)	16	IEC309	C13, C19	36, 6	55	1727	51	11,085	33	18	7
MT3 - 10668	400/3P (230/1P)	16	IEC309	UK	18	55	1727	51	11,085	33	18	7
MT3 - 10669	400/3P (230/1P)	16	IEC309	C13, C19, UK	24, 3, 3	55	1727	51	11,085	33	18	7

Vertical Power Distribution Units (Metered, RS 232)

Part Number	Source		Power Lead	Outlets		Dimensions			Power * Watts	Estimated Server Quantity **		
	Volts	Amps	Plug	Type	Qty	W mm	Hmm	D mm		550w	1,000w	2,500w
MT3 - 10670	400/3P (230/1P)	16	IEC309	C13	45	55	1727	51	11,085	33	18	
MT3 - 10671	400/3P (230/1P)	16	IEC309	C13, C19	36, 6	55	1727	51	11,085	33	18	7
MT3 - 10672	400/3P (230/1P)	16	IEC309	UK	15	55	1727	51	11,085	33	18	7
MT3 - 10673	400/3P (230/1P)	16	IEC309	C13, C19, UK	24, 3, 3	55	1727	51	11,085	33	18	7

Standard cord length is 3M

* Per rating per source; 100% power utilisation

** Reflects estimated 60% diversity factor (estimated performance)